

PENGUMUMAN PELELANGAN TERBUKA

NOMOR 492.U.Peng/SCM/PLN-NPS/2026

TENTANG

PENGADAAN PENGGANTIAN MOV BOILER DAN TURBIN PLTU ANGGREK - AI 2026

Tim Pengadaan Barang/Jasa PT PLN Nusantara Power Services akan melaksanakan Pelelangan Pengadaan Penggantian MOV Boiler dan Turbin PLTU Anggrek - AI 2026 dengan persyaratan sebagai berikut :

1. Persyaratan Peserta Lelang

- a. Terdaftar dalam Database Penyedia Barang / Jasa PT PLN Nusantara Power Services dalam Vendor Management System (VMS) dengan data yang telah terupdate atau sedang dalam proses pengurusan.
- b. Merupakan perusahaan yang telah memenuhi kewajiban perpajakan tahun terakhir.
- c. Merupakan pabrikan / agen / distributor atau perusahaan yang didukung oleh pabrikan / agen / distributor yang memiliki pengalaman suplai material dan jasa penggantian Aktuator, yang dibuktikan dengan : Melampirkan bukti Surat Tanda Pendaftaran (STP) keagenan dari Disperindag atau surat tanda pendaftaran sebagai distributor barang produksi luar negeri; Surat dukungan dari Manufacture / Agen / Distributor resmi yang ada di Indonesia; Memiliki kantor perwakilan di Indonesia serta memiliki engineer/teknisi ahli aktuator (brand yang ditawarkan) berdomisili di Indonesia untuk memudahkan mobilisasi maupun komunikasi dalam masa proyek, pemeliharaan maupun setelahnya (After Sales)
- d. Merupakan perusahaan yang mampu menjamin seluruh part yang didatangkan adalah baru (new product) beserta garansinya, bertanggung jawab sepenuhnya kualitas baik terhadap cacat terlihat maupun cacat tersembunyi.
- e. Memiliki bukti pendaftaran CSMS di PT PLN Group atau BUMN/Surat keterangan lolos/Sertifikat CSMS PT PLN Nusantara Power Group atau PT PLN (persero) yang masih berlakudengan kategori risiko Moderate.
- f. Memiliki pengalaman pengadaan Penggantian MOV Boiler Dan Turbin PLTU minimal 2 (dua) kali dalam kurun waktu 2 (dua) tahun terakhir dibuktikan dengan:
 - a. Surat Perintah Kerja/Kontrak Pekerjaan; atau
 - b. Berita Acara Pemeriksaan Barang;
 - c. Customer Satisfaction Letter / Customer Letter Reference Letter / Accomplishment Letter / Supporting Letter dari Presentative indonesia yang dikeluarkan dan diketahui oleh Customer terkait atau List pekerjaan yang pernah dilakukan;
- g. Salinan sertifikat ISO 9001, ISO 14001, dan OHSAS 18001 atau ISO 45001 atau SMK3 mengenai sistem Manajemen Keselamatan dan Kesehatan kerja yang dikeluarkan oleh badan sertifikasi yang terakreditasi dan masih berlaku.

2. Pelaksanaan Pengadaan

- a. Pendaftaran dan Pengambilan Dokumen :

Hari/Tanggal : Kamis, 23 Juli 2026 sd Senin, 03 Agustus 2026

Waktu : Pukul 08:00 s/d 13:00 WIB

Tempat : - PT. PLN Nusantara Power Services

Jl. Raya Bandara Juanda No 17

Desa Semambung, Gedangan

Sidoarjo

- Atau melalui email : pengadaan@plnnpowerservices.com

dengan diberi subyek :

SURAT PERNYATAAN MINAT PENGADAAN PENGGANTIAN MOV BOILER DAN TURBIN PLTU ANGGREK - AI 2026

- b. Aanwijzing atau Penjelasan Dokumen:

Hari/Tanggal : Senin, 27 Juli 2026

Waktu : Pukul 09:00 WIB

Tempat : - PT. PLN Nusantara Power Services

Jl. Raya Bandara Juanda No 17

Desa Semambung, Gedangan

Sidoarjo

- Atau Pelaksanaan penjelasan lelang dapat dilakukan melalui

media daring atau Internet (email, video conference,
dan lain-lain) yang akan diinformasikan berikutnya.

c. Dokumen Pengadaan dapat di-email atau diambil dalam bentuk soft copy.

3. Spesifikasi Pekerjaan
Sesuai daftar Terlampir

Demikian disampaikan untuk menjadi perhatian.

Sidoarjo, 22 Juli 2026

Tim Pengadaan Barang/Jasa PT. PLN Nusantara Power Services

Catatan :

Peserta yang mendaftar diharapkan membawa flashdisk apabila membutuhkan softcopy dokumen

PIC Pengadaan : BENI NURDIANSAH

No. HP :

BILL OF QUANTITY (BOQ)
Pengadaan Penggantian MOV Boiler dan Turbin PLTU Anggrek - AI 2026

No	ITEM BARANG/JASA	Jumlah	Satuan
1.	ACTUATOR VALVE BOILER BYPASS FEEDWATER REGULATING Multi-turn actuator Variable Speed Voltage : 1ph/220-240V/50Hz Duty : S2-15min short-time duty, classes A and B acc. to EN 15714-2 Linear thrust unit, stroke max. 100mm Valve attachment: 23 kN 30.0 - 300.0 mm/min Flow type : Water Control type : Regulating Operated : Handwell, push button local dan ccr Protection : IP-68 Double Shield BRAND OECD REF BRAND : AUMA / LIMITTORQUE/ ROTORK	2	Set
2.	ACTUATOR VALVE SPRAY DESUPERHEATER Multi-turn actuator Variable Speed Voltage : 1ph/220-240V/50Hz Duty : S2-15min short-time duty, classes A and B acc. to EN 15714-2 Linear thrust unit, stroke max. 50mm Valve attachment: 11.5 kN 27.7 mm/min Flow Type : Steam Control type : Regulating Operated : Handwell, Push Button local dan CCR Protection : IP-68 Double Shield BRAND OECD REF BRAND : AUMA / LIMITTORQUE/ ROTORK	2	Set
3.	ACTUATOR CONDENSER MAKE-UP WATER Multi Actuator Fixed Speed Voltage : 3ph/380V/50Hz Duty : S2-15min short-time duty, classes A and B acc. to EN 15714-2 Protection : IP-68 Double Shield Actuator Control Valve Attachment : 250 Nm II 45min-1 Flow Type : Water Control Type : Shutoff BRAND OECD REF BRAND : AUMA / LIMITTORQUE/ ROTORK	1	Set
4.	ACTUATOR OUTLET HPH Multi-turn actuator Fixed Speed Voltage : 3ph/380V/50Hz Duty : S2-15min short-time duty, classes A and B acc. to EN 15714-2 Protection : IP-68 Double Shield Valve attachment: 2000 Nm 22 min ¹ _g Flow Type : Water Control type : Shut-off BRAND OECD REF BRAND : AUMA / LIMITTORQUE/ ROTORK	1	Set

5. ACTUATOR THREEWAY VALVE HPH Multi-turn actuator Fixed Speed Voltage : 3ph/380V/50Hz Duty : S2-15min short-time duty, classes A and B acc. to EN 15714-2 Protection : IP-68 Double Shield Valve attachment: 2000 Nm 22 min ¹ Include : Interface Remote Module Integrated + Extend Module Control Flow Type : Water Control type : Shut-off BRAND OECD REFF BRAND : AUMA / LIMITTORQUE/ ROTORK	1	Set
6. ACTUATOR MAIN STEAM TO EXTRACTION 3 Multi-turn actuator Variable Speed Voltage : 3ph/380V/50Hz Duty : S2-15min short-time duty, classes A and B acc. to EN 15714-2 Protection : IP-68 Double Shield Valve attachment: 1000 Nm 22 min ¹ Flow Type : Steam Control type : Shut-off BRAND OECD REFF BRAND : AUMA / LIMITTORQUE/ ROTORK	1	Set
7. ACTUATOR RV MAIN STEAM TO EXTRACTION 3 Multi-turn actuator Variable Speed Voltage : 3ph/380V/50Hz Duty : S2-15min short-time duty, classes A and B acc. to EN 15714-2 Protection : IP-68 Double Shield Linear thrust unit, stroke max. 100mm Valve attachment: 11.5 kN 54.55 mm/min Flow Type : Steam Control type : Regulating BRAND OECD REFF BRAND : AUMA / LIMITTORQUE/ ROTORK	1	Set
8. ACTUATOR RV FEEDWATER TO MAIN STEAM Multi-turn actuator Variable Speed Voltage : 3ph/380V/50Hz Duty : S2-15min short-time duty, classes A and B acc. to EN 15714-2 Protection : IP-68 Double Shield Linear thrust unit, stroke max. 100mm Valve attachment: 11.5 kN 54.55 mm/min Flow Type : Water Control type : Regulating BRAND OECD REFF BRAND : AUMA / LIMITTORQUE/ ROTORK	1	Set
9. ACTUATOR OUTLET COOLING CONDENSOR Multi-turn actuator Fixed Speed Voltage : 3ph/380V/50Hz Duty : S2-15min short-time duty, classes A and B acc. to EN 15714-2 Protection : IP-68 Double Shield Valve attachment: 1000 Nm 90 min-1 Flow Type : Sea Water Control type : Shut-off BRAND OECD REFF BRAND : AUMA / LIMITTORQUE/ ROTORK	2	Set

10.	ACTUATOR HOT PRIMARY AIR PLENUM RIGHT SIDE & LEFT SIDE Part-turn actuator Fixed Speed Voltage : 3ph/380V/50Hz Duty: S2-15min short-time duty, classes A and B acc. To EN 15714-2 Valve attachment: max. 2400 Nm 48.0 s / 90° Flow Type : Air atmosfer Control type : Regulating BRAND OECD REFF BRAND : AUMA / LIMITTORQUE/ ROTORK	4	Set
11.	ACTUATOR DAMPER INLET ID FAN Multi-turn actuator Variable Speed Voltage : 3ph/380V/50Hz Duty : S2-15min short-time duty, classes A and B acc. to EN 15714-2 Protection : IP-68 Double Shield Lever gearbox Valve attachment: 4000 Nm 34.7 s / 90° Flow type : Air Atmosfer Control type : Regulating BRAND OECD REFF BRAND : AUMA / LIMITTORQUE/ ROTORK	2	Set
12.	ACTUATOR DAMPER INLET ID FAN Multi-turn actuator Variable Speed Voltage : 3ph/380V/50Hz Duty : S2-15min short-time duty, classes A and B acc. to EN 15714-2 Protection : IP-68 Double Shield Lever gearbox Valve attachment: 4000 Nm 34.7 s / 90° Flow type : Air Atmosfer Control type : Regulating BRAND OECD REFF BRAND : AUMA / LIMITTORQUE/ ROTORK	1	Set
13.	ACTUATOR DAMPER INLET PA FAN Multi-turn actuator Variable Speed Voltage : 3ph/380V/50Hz Duty : S2-15min short-time duty, classes A and B acc. to EN 15 Protection : IP-68 Double Shield 714-2 Lever gearbox Valve attachment: 4000 Nm 34.7 s / 90° Flow type : Air Atmosfer Control type : Regulating BRAND OECD REFF BRAND : AUMA / LIMITTORQUE/ ROTORK	1	Set
14.	ACTUATOR DAMPER INLET SA FAN Multi-turn actuator Variable Speed Voltage : 3ph/380V/50Hz Duty : S2-15min short-time duty, classes A and B acc. to EN 15714-2 Protection : IP-68 Double Shield Lever gearbox Valve attachment: 4000 Nm 34.7 s / 90° Flow type : Air Atmosfer Control type : Regulating BRAND OECD REFF BRAND : AUMA / LIMITTORQUE/ ROTORK	1	Set

15.	Accessories Accesorie termasuk : BOLT, NUT, AND SPRING WASHER, CABLE 8 X 1.0mm, CABLE 4 X 2.5mm, GLAND CABLE, FLEKSIBLE CONDUIT, CONNECTOR FLEKSIBLE CONDUIT, COUPLING MOV, SUPPORT MOV, SCUN	1	Set
16.	Jasa Pemasangan (Instalasi Aktuator 21 Item Aktuator)	1	Lot